

MT 50

Robust and easy to use, the MT50 is the ideal choice for manual testing – from multi-parameter analysis to “hardness only” tests of all types of shapes, sizes, and materials.

SOTAX



Manual Tablet Hardness Tester



MT50 — It doesn't get any easier.



sotax.com/MT50

FastTest™ thickness station for
efficient multi-parameter measuring

Intuitive icon-based EasyTouch™
control with user administration

SmartWay™ networking and data
management with q-doc®

Configurable test reports and various
printer interfaces including export of
test results to USB flash drive

5 parameters

Simple operation

Robust and precise
up to 800 N

Dr. Schleuniger®
technology

Electronic data
management

Recording of weight
measurements from external
analytical balance

Width / Length (Diameter) / Hardness
station with optimized jaw movements for
highest precision and short cycle times

SmartProtect™


Exchangeable tongues for
easy tablet orientation

Debris collection bin





All sizes, shapes, and materials.



Your application?

The MT50 is designed for testing almost anything. From pharmaceutical dosage forms to catalysts, pellets, extruded materials, and more. Robust Dr. Schleuniger® technology paired with powerful state-of-the-art electronics provide for highly accurate and repeatable hardness results up to 800 N. Low breaking forces (< 10 N) associated with small and brittle test samples are precisely measured using a special "sensitive mode".

100% flexible.

The highly accessible test area accepts all types of shapes, sizes, and materials. Optimized jaw movements provide short cycle times, while quick-change tongues allow for simple tablet handling by the operator. Clip-on jaws further extend the MT50 testing capabilities for 3-point bending strength tests or other testing methods.



Quick-change tongue with groove
for easy alignment of convex shapes



Extended jaw for testing large
objects up to 65 mm



Quick-change tongue with flat surface



Clip-on jaws for 3-point bending strength test



EasyTouch™

Available in your local language, the MT50 user interface is all about easy operation. Operators simply select a product and press "START" – ensuring that tests are always performed according to predefined methods. Additionally, simple quick-tests can be performed anytime. Different access levels make sure that settings or product specifications can only be modified by authorized personnel.



Fast, Faster, FastTest™


Simply the fastest way to perform a series of measurements. Equipped with an integrated thickness gauge, the MT50 becomes a true multi-purpose testing system that accumulates weight, thickness, width, length / diameter, and hardness results in a single test protocol. With little practice, operators can execute multi-parameter runs quicker and easier than with any other manual tester on the market.

Reporting.

A test protocol is automatically generated and printed at the end of each test. Results for all tested parameters including statistical analysis are presented in a clearly structured format. If pre-programmed products have been used, the printout includes all specifications and indicates whether limit violations (T1 / T2 / PL) have occurred. Report templates can be easily configured to individual requirements – from comprehensive test protocols to very basic reporting needs.

Networking the SmartWay™

The MT50 can be networked without requiring a computer to be located next to the unit. Test runs are automatically sent from q-doc® data management software to one or multiple testers via Ethernet connection. The operator only presses the "START" button on the MT50 display and performs the test. All results are automatically recorded in a central SQL database for full traceability and consolidated batch reporting.



Make life easier.



Daily functional check?

Quickly check the hardness station of your MT50 before starting daily tasks. Sometimes referred to as "mechanical tablet", the function checking device FCD™ is calibrated to simulate the breaking of a tablet at a defined force. Simply place the FCD™ in the MT50 test area and start the automated checking routine. If required, a report including "pass/fail" evaluation can be printed on completion.



DQD™ dynamic qualification.

Using a fully traceable and certified high-precision load cell, the entire hardness range can be qualified using the DQD™ qualification tool. A fully automated routine allows to adjust and verify the complete measuring range on multiple points without requiring static reference weights. Ask your local sales and service partner for more information on available SOTAX Premium Services.

MT50 Technical Specifications

| | | |
|---------------------------|--|--|
| Weight (Mass) | External balance | Mettler Toledo® / Sartorius® |
| | Units of measure | mg / g |
| | Resolution | 1.0 mg / 0.1 mg / 0.01 mg |
| Thickness | Units of measure | mm / inch |
| | Resolution | 0.01 mm |
| | Measuring range | 2 – 25 mm |
| | Repeatability | ± 0.03 mm |
| Width / Length (Diameter) | Units of measure | mm / inch |
| | Resolution | 0.01 mm |
| | Measuring range | 2 – 35 mm / optional: up to 65 mm |
| | Repeatability | ± 0.03 mm |
| Hardness | Units of measure | N / Kp / Sc / UDF |
| | Measuring range | 2 – 800 N |
| | Repeatability | ± 1 N |
| | Dr. Schleuniger® S-beam load cell | 99.98% linearity, over entire measuring range |
| | Calibration (Adjustment / Verification) | Static: with reference weights; dynamic: with DQD™ |
| Measuring principle | Constant speed | 0.05 – 5 mm/s, programmable |
| | Linear force increase | 10 – 200 N/s, programmable |
| Printer | PostScript® 3 (PS3) | Ethernet, USB |
| | Epson® 40col. | RS-232 serial |
| Interfaces | Ethernet, 2 × USB, 3 × RS-232 serial | |
| Power supply | 100 – 240 V / 50 – 60 Hz | |
| CE Conformity | The MT50 fully complies with all CE and EMC equipment guidelines relative to mechanical and electrical safety and electromagnetic compatibility. | |

| | | Standard | Easy |
|-----------------|--|---|------|
| Configuration | Weight (Mass), with external balance | ○ | – |
| | Thickness, with integrated FastTest™ | ○ | ○ |
| | Width | ○ | – |
| | Length (Diameter) | ○ | ○ |
| | Hardness | ● | ● |
| EasyTouch™ | Program capacity | 100 products | – |
| | User administration | ● | ● |
| | Xport™ option (export on USB flash drive) | ○ | – |
| Data Management | q-doc® software, with SmartWay™ networking | ○ | – |
| Weight | (without packaging) | 10 kg (22 lbs) | |
| Dimensions | Width | 404 mm (15.9 inch); with 65 mm option: 434 mm (17.1 inch) | |
| | Depth | 288 mm (11.4 inch) | |
| | Height | 177 mm (7.0 inch); with FastTest™: 207 mm (8.2 inch) | |

● included / required
○ optional

Technical specifications are subject to change without prior notice. Products illustrated in this brochure may include options or modifications not fitted as standard. No liability for errors and omissions.

